

Model	GX	GS
Frame Colour	Electric Blue (uniform), Matt Black (uniform), White/Black (Two Tone Gloss White front frame & gloss black Cleandrive)	White/Black (Two Tone Gloss white front frame & gloss black Cleandrive), White/Red (Two Tone Gloss white front frame & gloss red Cleandrive), Grey/Black (Two Tone Gloss grey front frame & gloss black Cleandrive), White/Blue (Two Tone Gloss white front frame & gloss blue Cleandrive)
Frame Material	Hydro-formed 6061 T6 alloy front frame with injection moulded magnesium Cleandrive	Injection Moulded Magnesium
PitstopWheel [®]	Magnesium with center hub mount	Magnesium with patented PitstopLock™ system
PitstopWheel [®] Colour	Gloss Black	Gloss Black
Motor Drive Control	Pedal Torque Sensing	Pedal Torque Sensing
Daytime Running Light (DRL)**	No	No
Smart Device Connectivity	GocycleConnect [™] App via wireless Bluetooth [®]	GocycleConnect [™] App via wireless Bluetooth [®]
Riding Modes	City, Eco, On-Demand, Custom. Multiple, programmable through GocycleConnect™ App	City, Eco, On-Demand, Custom. Multiple, programmable through GocycleConnect™ App
Electric Drive Speed***	20 mph / 25 kph	20 mph / 25 kph
Range	Up to 65km (40 miles), depending on pedal input	Up to 65km (40 miles), depending on pedal input
Motor****	Gocycle proprietary front hub motor gear drive with traction control 500 watt US / 250 watt EU continuous	Gocycle proprietary front hub motor gear drive with traction control 500 watt US / 250 watt EU continuous
Battery*****	Quick removable lithium ion: 13.7Ah, 22V, approx 300 Wh	In frame lithium ion: 13.5Ah, 22V, approx 300 Wh
Charging Time	7 hours (3.5 hours with optional fast charger)	7 hours (3.5 hours with optional fast charger)
Motor Controller	Gocycle proprietary	Gocycle proprietary
Handlebar Display	LED Fuel Gauge or with Smart Device and GocycleConnect™ App	With Smart Device and GocycleConnect™ App
Shifting	Mechanical Microshift™	Mechanical Microshift™
Transmission	Patented Cleandrive [™] Shimano Nexus 3-speed	Patented Cleandrive [™] Shimano Nexus 3-speed
Gear Inches	1st=39.1 in, 2nd=53.3 in, 3rd=72.5 in	1st=39.1 in, 2nd=53.3 in, 3rd=72.5 in
Gear Development	1st=3.1 m, 2nd=4.3 m, 3rd=5.8 m	1st=3.1 m, 2nd=4.3 m, 3rd=5.8 m
Brakes	Hydraulic disk, front and rear	Hydraulic disk, front and rear
Tyres	Gocycle All Weather Tyre (406-54, 20 x 2.25 in)	Gocycle All Weather Tyre (406-54, 20 x 2.25 in)
Front Motor Fork	Gocycle proprietary, single-sided, 6061 T6, fixed	Gocycle proprietary, single-sided, 6061 T6, Uni-form 3D Forged
Rear Suspension	Gocycle Lockshock™ 25mm (1 in) travel	Gocycle Lockshock™ 25mm (1 in) travel
Saddle	Velo Sport	Velo Sport
Seat Post	34.9 mm Aluminium	34.9 mm Aluminium
Pedals	Gocycle Folding Standard	Gocycle Folding Standard
Grips	Gocycle Sport Ergo	Gocycle Sport Ergo
Frame Size and Fit	Universal Vgonomic™	Universal Vgonomic™
Handlebar Stem	Quick Folding	Reach adjustment
Head Angle	70°	70°
Seat Tube Angle	68°	68°
Wheelbase	1065mm (42 in)	1065mm (42 in)
Bottom Bracket Height	275mm (11.5 in)	275mm (11.5 in)
Folding Method	Fast Folding frame and handlebar	Seperable wheels and seat assembly with folding handlebar
Stowable Dimensions	Kickstand down: L830mm x W390mm x H750mm (L32.7in x W15.3in x H29.5in) with folding pedals folded Kickstand up: L880mm x W390mm x H615mm (L34.6in x W15.3in x H24.2in) with folding pedals folded	Portable Docking Station for easy stowing and transport x H580mm L30.7in x W14.6in x H22.8in) (L780mm x W370mm
Approximate Weight*****	17.8kg (39.2 lbs)	16.0kg (35.3 lbs)
Maximum Rider Weight*****	100kg (220 lbs), including clothing and luggage	100kg (220 lbs), including clothing and luggage