

CHASER RX

Teal Green / Black



FRAME STEALTH ALLOY • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT750Wh • **FORK** ROCKSHOX PSYLO SILVER, 160mm • **REAR SHOCK** ROCKSHOX DELUXE SELECT R • **SEATPOST** ONOFF PIJA ADJUSTABLE LENGTH • **BRAKES** SRAM DB8 • **WHEELS** MDK-HP1 • **REAR DERAILLEUR** SRAM GX EAGLE

CHASER RX

Teal Green / Black

FRAME	Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 140mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm
REAR SHOCK	RockShox Deluxe Select R DebonAir, 205x60mm. Settings: Low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings
SHOCK SETTINGS	Light compression, Linear rebound, 1 Token
FORK	RockShox Psylo Silver 29, 160mm, Motion control damper, Solo Air, tapered steerer tube, Boost 15x110mm axle, 35mm steel stanchions, 44mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload
FORK REMOTE	--
HEADSET	Onoff ZS44/ZS56, 1-1/8", 1.5" head tube, ACB sealed bearings, top 42x30x7x45°x45°, bottom 52x40x8x45°x45°
STEM	Onoff S3 30mm 0°, 6061 forged alloy, 31.8mm barbore
HANDLEBAR	Onoff S3 1.0 6061 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbore. L and XL size: 1.5 rise
GRIPS	Onoff Beehive, 1lock-on, 135mm
SEATPOST	Onoff Pija dropper internal, diameter 31.6mm, 1X Remote lever with bearing, S size: 140-115mm (388-235mm), M size: 160-135mm (428-255mm), L size: 180-155mm (468-275mm), XL size: 210-185mm (528-305mm)
SADDLE	MDK urban
FRONT BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
REAR BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
BRAKE LEVER	Sram DB8, tool reach adjust, lever pivot bushings
RIMS	MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes
SPOKES	CN round stainless steel

FRONT HUB	Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
REAR HUB	Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts, HG freehub
FRONT TIRE	Maxxis Ikon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
REAR TIRE	Maxxis Ikon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
CRANKSET	Race Face Aeffect-R ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
BOTTOM BRACKET	--
PEDALS	Urban pedal resin black
CHAIN	Sram SX Eagle, 12s, Powerlock
FRONT DERAILLEUR	--
REAR DERAILLEUR	Sram GX Eagle, 12s
SHIFT LEVERS	Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram PG-1210, 11-50T, 12s
MOTOR	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
BATTERY	Bosch Powertube 750Wh
DISPLAY	Bosch Kiox 500 / Bosch Mini Remote / Bosch System Controller
DERAILLEUR HANGER	Sram UDH
OTHERS	Front light: 150LUX output DC 6-12V, waterproof Alloy cage. Rear Light: Fender Mount, w/ Reflective, e-bike version, 6-12V. Fenders: Alloy black MDK custom fenders. Rack: Alloy MDK rear Rack, Max loading 25kg. Kickstand: Massload KSA18-40
WEIGHT	--