



## e-MTB ENDURO / CRAFTY CARBON XR

Mars / Black

<b>FRAME</b>	Crafty Stealth Air full Carbon, Updated Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers	<b>FRONT HUB</b>	Mavic, Boost 15x110mm, IS 6 bolts
<b>SIZES</b>	S: 380mm / M: 410mm / ML: 435mm / L: 460mm / XL: 490mm	<b>REAR HUB</b>	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub
<b>REAR SHOCK</b>	Öhlins TTX22M.2 185x55mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, spring preload. Trunnion top mount, 30x8mm bottom bushings	<b>FRONT TIRE</b>	Maxxis Assegai 29x2.6WT, tubeless ready, 3C MAXX GRIP compound, DD protection, 60x2TPI, folding bead
<b>SHOCK SETTINGS</b>	C10 compression, R20 rebound. Spring rate: S size 411 lbs, size M 457 lbs, ML size 502 lbs, L size 548 lbs, XL size 605 lbs	<b>REAR TIRE</b>	Maxxis Minion DHR II 29x2.6 WT, tubeless ready, 3C MaxxTerra compound, DD protection, 2x120TPI, folding bead
<b>FORK</b>	Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber	<b>CRANKSET</b>	E.13 Helix Race Carbon E*Spec Plus, All sizes: 160mm
<b>FORK REMOTE</b>	--	<b>RINGS</b>	Sram X-Sync 2 Eagle 34T T-Type, steel, narrow-wide, 104 BCD CL55
<b>HEADSET</b>	Acros custom ZS56/ZS56, 1-1/8", 1.5" head tube, Internal cable routing, sealing plugs without blocklock	<b>BOTTOM BRACKET</b>	--
<b>STEM</b>	Onoff S9 30mm 0°, Full CNC, 31.8mm barbore	<b>PEDALS</b>	--
<b>HANDLEBAR</b>	Onoff S6 1.0 Carbon, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbore. L and XL size: 1.5 rise	<b>CHAIN</b>	Sram GX Eagle T-Type, 12s, Powerlock
<b>GRIPS</b>	Onoff Desert Pro, CNC lock-on, 135mm. L and XL: Thicker size	<b>FRONT DERAILLEUR</b>	--
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, IX Remote lever with bearing, S size: 140-115mm (388-235mm), M size: 160-135mm (428-255mm), ML size: 180-155mm (468-275mm), L size: 210-185mm (528-305mm), XL size: 210-185mm (528-305mm)	<b>REAR DERAILLEUR</b>	Sram X0 Eagle AXS, T-Type, 12s
<b>SADDLE</b>	Ergon SM-10	<b>SHIFT LEVERS</b>	Sram Eagle AXS Pod MMX, 12s
<b>FRONT BRAKE</b>	Sram Maven Silver, 18 and 19.5-millimeter 4-piston caliper, Centerline 220mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	<b>CASSETTE</b>	Sram XS-1295, 10-52T, T-Type, 12s
<b>REAR BRAKE</b>	Sram Maven Silver, 18 and 19.5-millimeter 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	<b>MOTOR</b>	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
<b>BRAKE LEVER</b>	Sram Maven Silver, SwingLink and lever pivot bushings, tools-free reach adjust	<b>BATTERY</b>	Bosch Powertube 600Wh
<b>RIMS</b>	Mavic E-Deemax S 29, 30mm internal width, Maxtal welded, PFP, tubeless, 28 spokes	<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>SPOKES</b>	Mavic straight-pull double butted, contactless lacing	<b>DERAILLEUR HANGER</b>	--
		<b>OTHERS</b>	--
		<b>WEIGHT</b>	--



## e-MTB ENDURO / CRAFTY CARBON RR

Earth Red / Black / Flame Red

<b>FRAME</b>	Crafty Stealth Air full Carbon front triangle, Stealth Alloy rear triangle, Updated Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers	<b>REAR HUB</b>	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, XD freehub
<b>SIZES</b>	S: 380mm / M: 410mm / ML: 435mm / L: 460mm / XL: 490mm	<b>FRONT TIRE</b>	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>REAR SHOCK</b>	Fox Float X Factory Kashima EVOL, 185x55mm. Settings: 2-position compression (Open/Firm), rebound, air preload. Trunnion top mount, 30x8mm bottom bushings	<b>REAR TIRE</b>	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>SHOCK SETTINGS</b>	CS40 compression, RL60 rebound, Rezi B40, LML, 0.2 volume spacer	<b>CRANKSET</b>	Race Face Aeffect-R ebike, 160mm
<b>FORK</b>	Fox 38 29 Float GRIPX2 Factory Kashima, 160mm, tapered steerer tube, Boost 15x110mm Kabolt axle, 44mm offset. Settings: high and low-speed compression, high and low-speed rebound, air preload	<b>RINGS</b>	Sram X-Sync 2 Eagle 34T T-Type, steel, narrow-wide, 104 BCD CL55
<b>FORK REMOTE</b>	--	<b>BOTTOM BRACKET</b>	--
<b>HEADSET</b>	Acros custom ZS56/ZS56, 1-1/8", 1.5" head tube, Internal cable routing, sealing plugs without blocklock	<b>PEDALS</b>	--
<b>STEM</b>	Onoff S6 30mm 0°, 6061 forged alloy + CNC, 31.8mm barbare	<b>CHAIN</b>	Sram GX Eagle T-Type, 12s, Powerlock
<b>HANDLEBAR</b>	Onoff S6 1.0 7050 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbare. L and XL size: 1.5 rise	<b>FRONT DERAILLEUR</b>	--
<b>GRIPS</b>	Onoff Forest, CNC lock-on, 135mm	<b>REAR DERAILLEUR</b>	Sram GX Eagle AXS, T-Type, 12s
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, 1X Remote lever with bearing, S size: 140-115mm (388-235mm), M size: 160-135mm (428-255mm), ML size: 180-155mm (468-275mm), L size: 210-185mm (528-305mm), XL size: 210-185mm (528-305mm)	<b>SHIFT LEVERS</b>	Sram Eagle AXS Pod MMX, 12s
<b>SADDLE</b>	Ergon SM-10	<b>CASSETTE</b>	Sram XS-1275, 10-52T, T-Type, 12s
<b>FRONT BRAKE</b>	Sram Maven Bronze, 18 and 19.5-millimeter 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	<b>MOTOR</b>	New Bosch Performance Line CX Cruise (25Kw/h) GEN4 SMART SYSTEM (BDU384Y)
<b>REAR BRAKE</b>	Sram Maven Bronze, 18 and 19.5-millimeter 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	<b>BATTERY</b>	Bosch Powertube 800Wh
<b>BRAKE LEVER</b>	Sram Maven Bronze, SwingLink and lever pivot bushings, tools-free reach adjust	<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>RIMS</b>	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes	<b>DERAILLEUR HANGER</b>	--
<b>SPOKES</b>	Mavic J-bend double butted, contactless lacing	<b>OTHERS</b>	--
<b>FRONT HUB</b>	Mavic, Boost 15x110mm, IS 6 bolts	<b>WEIGHT</b>	--



## e-MTB ENDURO / CRAFTY CARBON R

Black / Nimbus Grey / Tonic Gold

<b>FRAME</b>	Crafty Stealth Air full Carbon front triangle, Stealth Alloy rear triangle, Updated Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers
<b>SIZES</b>	S: 380mm / M: 410mm / ML: 435mm / L: 460mm / XL: 490mm
<b>REAR SHOCK</b>	Fox Float-X LV Performance, 185x55mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings
<b>SHOCK SETTINGS</b>	CS40 compression, RL60 rebound, Rezi B40, LML, 0.2 volume spacer
<b>FORK</b>	Fox 38 29 Float GRIP Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
<b>FORK REMOTE</b>	--
<b>HEADSET</b>	Acros custom ZS56/ZS56, 1-1/8", 1.5" head tube, internal cable routing, sealing plugs without blocklock
<b>STEM</b>	Onoff S6 30mm 0°, 6061 forged alloy + CNC, 31.8mm bar bore
<b>HANDLEBAR</b>	Onoff S6 1.0 7050 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm bar bore. L and XL size: 1.5 rise
<b>GRIPS</b>	Onoff Forest, CNC lock-on, 135mm
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, IX Remote lever with bearing, S size: 140-115mm (388-235mm), M size: 160-135mm (428-255mm), ML size: 180-155mm (468-275mm), L size: 210-185mm (528-305mm), XL size: 210-185mm (528-305mm)
<b>SADDLE</b>	Ergon SM-10
<b>FRONT BRAKE</b>	Shimano XT M8120, 4 piston caliper, MT800 ICE-Tech 203mm CenterLock rotor, resin pads with fin
<b>REAR BRAKE</b>	Shimano XT M8120, 4 piston caliper, MT800 ICE-Tech 203mm CenterLock rotor, resin pads with fin
<b>BRAKE LEVER</b>	Shimano XT M8100, ergonomic antiskid lever with servo wave, tool less reach adjust, free stroke adjust
<b>RIMS</b>	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
<b>SPOKES</b>	Mavic J-bend double butted, contactless lacing
<b>FRONT HUB</b>	Mavic, Boost 15x110mm, IS 6 bolts

<b>REAR HUB</b>	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, MS freehub
<b>FRONT TIRE</b>	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>REAR TIRE</b>	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>CRANKSET</b>	Race Face Aeffect-R ebike, 160mm
<b>RINGS</b>	Race Face, 34T, steel, direct mount
<b>BOTTOM BRACKET</b>	--
<b>PEDALS</b>	--
<b>CHAIN</b>	Shimano XT M8100, 12s
<b>FRONT DERAILLEUR</b>	--
<b>REAR DERAILLEUR</b>	Shimano XT M8100, SGS, Shadow+
<b>SHIFT LEVERS</b>	Shimano XT M8100, Rapid Fire Plus, 12s
<b>CASSETTE</b>	Shimano XT M8100 10-51T Hyperglide+, 12s
<b>MOTOR</b>	New Bosch Performance Line CX Cruise (25Kw/h) GEN4 SMART SYSTEM (BDU384Y)
<b>BATTERY</b>	Bosch Powertube 800Wh
<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>DERAILLEUR HANGER</b>	Sram UDH
<b>OTHERS</b>	--
<b>WEIGHT</b>	--



## e-MTB ENDURO / CRAFTY CARBON R

Bunker Grey / Fog Grey / Flame Red

<b>FRAME</b>	Crafty Stealth Air full Carbon front triangle, Stealth Alloy rear triangle, Updated Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers
<b>SIZES</b>	S: 380mm / M: 410mm / ML: 435mm / L: 460mm / XL: 490mm
<b>REAR SHOCK</b>	Fox Float-X LV Performance, 185x55mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings
<b>SHOCK SETTINGS</b>	CS40 compression, RL60 rebound, Rezi B40, LML, 0.2 volume spacer
<b>FORK</b>	Fox 38 29 Float GRIP Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload
<b>FORK REMOTE</b>	--
<b>HEADSET</b>	Acros custom ZS56/ZS56, 1-1/8", 1.5" head tube, Internal cable routing, sealing plugs without blocklock
<b>STEM</b>	Onoff S6 30mm 0°, 6061 forged alloy + CNC, 31.8mm barbore
<b>HANDLEBAR</b>	Onoff S6 1.0 7050 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbore. L and XL size: 1.5 rise
<b>GRIPS</b>	Onoff Forest, CNC lock-on, 135mm
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, IX Remote lever with bearing, S size: 140-115mm (388-235mm), M size: 160-135mm (428-255mm), ML size: 180-155mm (468-275mm), L size: 210-185mm (528-305mm), XL size: 210-185mm (528-305mm)
<b>SADDLE</b>	Ergon SM-10
<b>FRONT BRAKE</b>	Shimano XT M8120, 4 piston caliper, MT800 ICE-Tech 203mm CenterLock rotor, resin pads with fin
<b>REAR BRAKE</b>	Shimano XT M8120, 4 piston caliper, MT800 ICE-Tech 203mm CenterLock rotor, resin pads with fin
<b>BRAKE LEVER</b>	Shimano XT M8100, ergonomic antiskid lever with servo wave, tool less reach adjust, free stroke adjust
<b>RIMS</b>	Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes
<b>SPOKES</b>	Mavic J-bend double butted, contactless lacing
<b>FRONT HUB</b>	Mavic, Boost 15x110mm, IS 6 bolts

<b>REAR HUB</b>	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, MS freehub
<b>FRONT TIRE</b>	Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>REAR TIRE</b>	Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead
<b>CRANKSET</b>	Race Face Aeffect-R ebike, 160mm
<b>RINGS</b>	Race Face, 34T, steel, direct mount
<b>BOTTOM BRACKET</b>	--
<b>PEDALS</b>	--
<b>CHAIN</b>	Shimano XT M8100, 12s
<b>FRONT DERAILLEUR</b>	--
<b>REAR DERAILLEUR</b>	Shimano XT M8100, SGS, Shadow+
<b>SHIFT LEVERS</b>	Shimano XT M8100, Rapid Fire Plus, 12s
<b>CASSETTE</b>	Shimano XT M8100 10-51T Hyperglide+, 12s
<b>MOTOR</b>	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
<b>BATTERY</b>	Bosch Powertube 800Wh
<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>DERAILLEUR HANGER</b>	Sram UDH
<b>OTHERS</b>	--
<b>WEIGHT</b>	--