



## LIGHT e-MTB / DUNE XR

Black / Mars / Racing Silver

<b>FRAME</b>	Stealth Air full Carbon, Updated Zero Suspension System, Mullet, 165mm travel, Forward Geometry, internal & removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers.	<b>FRONT HUB</b>	e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts
<b>SIZES</b>	S: 380mm / M: 420mm / L: 450mm / XL: 490mm	<b>REAR HUB</b>	e*thirteen Boost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, XD freehub
<b>REAR SHOCK</b>	Öhlins TTX22M.2 205x65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, spring preload. Trunnion top mount, 30x8mm bottom bushings	<b>FRONT TIRE</b>	Maxxis Assegai 29x2.5WT, tubeless ready, 3C MaxxGrip compound, EXO+ casing, 60TPI, folding bead
<b>SHOCK SETTINGS</b>	C10 compression, R20 rebound. Spring rate: S size 343 lbs, M size 411 lbs, L size 457 lbs, XL size 502 lbs	<b>REAR TIRE</b>	Maxxis Minion DHR II 27.5x2.5WT, tubeless ready, 3C MaxxTerra compound, DD protection, 2x120TPI, folding bead
<b>FORK</b>	Öhlins RXF 38 M.2 29, 180mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber	<b>CRANKSET</b>	E.13 TRS Race carbon ebike, All sizes: 160mm
<b>FORK REMOTE</b>	--	<b>RINGS</b>	Sram X-Sync 2 Eagle 34T T-Type, steel, narrow-wide, 104 BCD CL55
<b>HEADSET</b>	Acros custom IS52/ZS56, 1-1/8", 1.5" head tube, Internal cable routing, sealing plugs without blocklock	<b>BOTTOM BRACKET</b>	--
<b>STEM</b>	Onoff S9 30mm 0°, Full CNC, 31.8mm barbore	<b>PEDALS</b>	--
<b>HANDLEBAR</b>	Onoff S9 1.0 Carbon, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbore. L and XL size: 1.5 rise	<b>CHAIN</b>	Sram XD Eagle T-Type, 12s, Powerlock
<b>GRIPS</b>	Onoff Desert Pro, CNC lock-on, 135mm. L and XL: Thicker size	<b>FRONT DERAILLEUR</b>	--
<b>SEATPOST</b>	RockShox Reverb Stealth AXS, diameter 31.6mm S size: 340x125mm M size: 390x150mm L size: 440x170mm XL size: 440x170mm	<b>REAR DERAILLEUR</b>	Sram XD Eagle AXS T-Type, 12s
<b>SADDLE</b>	Fizik Terra Aidon Slim X5	<b>SHIFT LEVERS</b>	Sram Eagle AXS Pod MMX, 12s
<b>FRONT BRAKE</b>	Sram Code Ultimate Stealth, oversized 4-piston caliper, HS2 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	<b>CASSETTE</b>	Sram XS-1295, 10-52T, T-Type, 12s
<b>REAR BRAKE</b>	Sram Code Ultimate Stealth, oversized 4-piston caliper, HS2 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	<b>MOTOR</b>	Bosch Performance Line SX (25Km/h) GEN4 SMART SYSTEM Diagonal, Wide
<b>BRAKE LEVER</b>	Sram Code Ultimate Stealth, SwingLink and lever pivot bearings, tools-free reach and contact point adjust	<b>BATTERY</b>	Bosch Compact Powertube 400Wh
<b>RIMS</b>	e*thirteen Grappler Carbon, Hookless carbon rim, 30mm internal width, tubeless ready, 28 spokes, 29 front, 27.5 rear	<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>SPOKES</b>	e*thirteen custom Hive triple-butted black steel, alloy nipples, nipple washers	<b>DERAILLEUR HANGER</b>	--
		<b>OTHERS</b>	--
		<b>WEIGHT</b>	--



## LIGHT e-MTB / DUNE RR

Bronze / Vortex Grey / Frog Grey

<b>FRAME</b>	Stealth Air full Carbon, Updated Zero Suspension System, Mullet, 165mm travel, Forward Geometry, internal & removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers	<b>FRONT HUB</b>	e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts
<b>SIZES</b>	S: 380mm / M: 420mm / L: 450mm / XL: 490mm	<b>REAR HUB</b>	e*thirteen Boost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, XD freehub
<b>REAR SHOCK</b>	Öhlins TTX Air 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 30x8mm bottom bushings	<b>FRONT TIRE</b>	Maxxis Assegai 29x2.5WT, tubeless ready, 3C MaxxGrip compound, EXO+ casing, 60TPI, folding bead
<b>SHOCK SETTINGS</b>	C10 compression, R20 rebound. Volume reducers 12.000 (2xF+1D)	<b>REAR TIRE</b>	Maxxis Minion DHR II 27.5x2.5WT, tubeless ready, 3C MaxxTerra compound, DD protection, 2x120TPI, folding bead
<b>FORK</b>	Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber	<b>CRANKSET</b>	E.13 Helix Core E*Spec Plus, All sizes: 160mm
<b>FORK REMOTE</b>	--	<b>RINGS</b>	Sram X-Sync 2 Eagle 34T T-Type, steel, narrow-wide, 104 BCD CL55
<b>HEADSET</b>	Acros custom IS52/ZS56, 1-1/8", 1.5" head tube, Internal cable routing, sealing plugs without blocklock	<b>BOTTOM BRACKET</b>	--
<b>STEM</b>	Onoff S6 30mm 0°, 6061 forged alloy + CNC, 31.8mm barbare	<b>PEDALS</b>	--
<b>HANDLEBAR</b>	Onoff S6 1.0 7050 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbare. L and XL size: 1.5 rise	<b>CHAIN</b>	Sram GX Eagle T-Type, 12s, Powerlock
<b>GRIPS</b>	Onoff Forest, CNC lock-on, 135mm	<b>FRONT DERAILLEUR</b>	--
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, 1X Remote lever with bearing, S size: 140-115mm (388-235mm), M size: 160-135mm (428-255mm), L size: 180-155mm (468-275mm), XL size: 210-185mm (528-305mm)	<b>REAR DERAILLEUR</b>	Sram GX Eagle AXS T-Type, 12s
<b>SADDLE</b>	Fizik Terra Aidon Slim X5	<b>SHIFT LEVERS</b>	Sram Eagle AXS Pod MMX, 12s
<b>FRONT BRAKE</b>	Sram Code Bronze Stealth, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	<b>CASSETTE</b>	Sram XS-1275, 10-52T, T-Type, 12s
<b>REAR BRAKE</b>	Sram Code Bronze Stealth, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	<b>MOTOR</b>	Bosch Performance Line SX (25Km/h) GEN4 SMART SYSTEM Diagonal, Wide
<b>BRAKE LEVER</b>	Sram Code Bronze Stealth, SwingLink and lever pivot bushings, tool-free reach adjust	<b>BATTERY</b>	Bosch Compact Powertube 400Wh
<b>RIMS</b>	e*thirteen Grappler Race, Hookless 6069 Welded Aluminum 30mm internal width, tubeless ready, 28F spokes 29 front, 27.5 rear"	<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>SPOKES</b>	e*thirteen custom J-bend, triple-butted steel, alloy nipples, nipple washers	<b>DERAILLEUR HANGER</b>	--
		<b>OTHERS</b>	--
		<b>WEIGHT</b>	--



## LIGHT e-MTB / DUNE R

Nimbus Grey / Obsidian Grey / Dense Yellow

<b>FRAME</b>	Stealth Air full Carbon, Updated Zero Suspension System, Mullet, 165mm travel, Forward Geometry, internal & removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 15mm axles, exclusive plastic motor covers	<b>FRONT HUB</b>	e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts
<b>SIZES</b>	S: 380mm / M: 420mm / L: 450mm / XL: 490mm	<b>REAR HUB</b>	e*thirteen Boost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, HG Freehub
<b>REAR SHOCK</b>	Fox Float X Performance EVOL, 205x65mm. Settings: 2-position compression (Open/Firm), rebound, air preload. Trunnion top mount, 30x8mm bottom bushings	<b>FRONT TIRE</b>	Maxxis Assegai 29x2.5WT, tubeless ready, 3C MaxxGrip compound, EXO+ casing, 60TPI, folding bead
<b>SHOCK SETTINGS</b>	Medium compression, medium rebound, air volume spacer 0.4	<b>REAR TIRE</b>	Maxxis Minion DHR II 27.5x2.5WT, tubeless ready, 3C MaxxTerra compound, DD protection, 2x120TPI, folding bead
<b>FORK</b>	FOX 38 Float 3P Performance Grip, 170mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload	<b>CRANKSET</b>	E.13 Helix Core E*Spec Plus, All sizes: 160mm
<b>FORK REMOTE</b>	--	<b>RINGS</b>	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
<b>HEADSET</b>	Acros custom IS52/ZS56, 1-1/8", 1.5" head tube, Internal cable routing, sealing plugs without blocklock	<b>BOTTOM BRACKET</b>	--
<b>STEM</b>	Onoff S6 30mm 0°, 6061 forged alloy + CNC, 31.8mm barbare	<b>PEDALS</b>	--
<b>HANDLEBAR</b>	Onoff S6 1.0 7050 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbare. L and XL size: 1.5 rise	<b>CHAIN</b>	Sram NX Eagle, 12s, Powerlock
<b>GRIPS</b>	Onoff Forest, CNC lock-on, 135mm	<b>FRONT DERAILLEUR</b>	--
<b>SEATPOST</b>	Onoff Pija dropper internal, diameter 31.6mm, 1X Remote lever with bearing, S size: 140-115mm (388-235mm), M size: 160-135mm (428-255mm), L size: 180-155mm (468-275mm), XL size: 210-185mm (528-305mm)	<b>REAR DERAILLEUR</b>	Sram GX Eagle, 12s
<b>SADDLE</b>	Fizik Terra Aidon Slim X5	<b>SHIFT LEVERS</b>	Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click
<b>FRONT BRAKE</b>	Sram DB8 stealth, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	<b>CASSETTE</b>	Sram PG-1230, 11-50T, 12s
<b>REAR BRAKE</b>	Sram DB8 stealth, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	<b>MOTOR</b>	Bosch Performance Line SX (25Km/h) GEN4 SMART SYSTEM Diagonal, Wide
<b>BRAKE LEVER</b>	Sram DB8, SwingLink and lever pivot bearings, tools-free reach and contact point adjust	<b>BATTERY</b>	Bosch Compact Powertube 400Wh
<b>RIMS</b>	e*thirteen Grappler Core, Hookless 6069 Welded Aluminum 30mm internal width, tubeless ready, 28F spokes 29 front, 27.5 rear	<b>DISPLAY</b>	Purion 400 / Bosch Mini Remote / Bosch System Controller
<b>SPOKES</b>	e*thirteen custom J-bend, triple-buttet steel, alloy nipples, nipple washers	<b>DERAILLEUR HANGER</b>	Sram UDH
		<b>OTHERS</b>	--
		<b>WEIGHT</b>	--