

PRIME X

Vortex Grey / Black / Earth Red



FRAME STEALTH ALLOY • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT625Wh • **FORK** ROCKSHOX RECON SILVER RL, 120mm • **BRAKES** SRAM LEVEL T • **WHEELS** MDK-HP1 • **REAR DERAILLEUR** SRAM SX EAGLE

PRIME X

Vortex Grey / Black / Earth Red

FRAME	Prime 6061 Xtralite Full Butted Alloy, Forward Geometry, internal removable battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor
SIZES	XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm
REAR SHOCK	--
SHOCK SETTINGS	--
FORK	RockShox Recon Silver RL 29, 120mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 32mm steel stanchions, 42mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload
FORK REMOTE	--
HEADSET	Onoff ZS44/ZS56, 1-1/8", 1.5" head tube, ACB sealed bearings, top 42x30x7x45°x45°, bottom 52x40x8x45°x45°
STEM	MDK Urban 40mm 5°, 6061 forged alloy, 31.8mm barbore
HANDLEBAR	Onoff S3 1.0 6061 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbore. L and XL size: 1.5 rise
GRIPS	Onoff Beehive, 1lock-on, 135mm
SEATPOST	Onoff S3 0-R, diameter 31.6mm, length 400mm
SADDLE	MDK urban
FRONT BRAKE	Sram Level T, 2 piece caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pad
REAR BRAKE	Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
BRAKE LEVER	Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings
RIMS	MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes
SPOKES	CN round stainless steel
FRONT HUB	Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
REAR HUB	Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts, HG freehub

FRONT TIRE	Maxxis Gritter 29x2.5, single compound, 60TPI, wire bead
REAR TIRE	Maxxis Gritter 29x2.5, single compound, 60TPI, wire bead
CRANKSET	Race Face Aeffect-R ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
BOTTOM BRACKET	--
PEDALS	Urban pedal resin black
CHAIN	Sram SX Eagle, 12s, Powerlock
FRONT DERAILLEUR	--
REAR DERAILLEUR	Sram SX Eagle, 12s
SHIFT LEVERS	Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram PG-1210, 11-50T, 12s
MOTOR	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
BATTERY	Bosch Powertube 625Wh
DISPLAY	Bosch Intuvia 100 / Bosch Mini Remote / Bosch System Controller
DERAILLEUR HANGER	Sram UDH
OTHERS	Front light: 150LUX output DC 6-12V, waterproof Alloy cage. Rear Light: Fender Mount, w/ Reflective, e-bike version, 6-12V. Fenders: Alloy black MDK custom fenders. Rack: Alloy MDK rear Rack, Max loading 25kg. Kickstand: Massload KSA18-40
WEIGHT	--

PRIME X

Bunker Grey / Fog Grey / Teal Green



FRAME STEALTH ALLOY • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT625Wh • **FORK** ROCKSHOX RECON SILVER RL, 120mm • **BRAKES** SRAM LEVEL T • **WHEELS** MDK-HP1 • **REAR DERAILLEUR** SRAM SX EAGLE

PRIME X

Bunker Grey / Fog Grey / Teal Green

FRAME	Prime 6061 Xtralite Full Butted Alloy, Forward Geometry, internal removable battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor
SIZES	XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm
REAR SHOCK	--
SHOCK SETTINGS	--
FORK	RockShox Recon Silver RL 29, 120mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 32mm steel stanchions, 42mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload
FORK REMOTE	--
HEADSET	Onoff ZS44/ZS56, 1-1/8", 1.5" head tube, ACB sealed bearings, top 42x30x7x45°x45°, bottom 52x40x8x45°x45°
STEM	MDK Urban 40mm 5°, 6061 forged alloy, 31.8mm barbore
HANDLEBAR	Onoff S3 1.0 6061 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbore. L and XL size: 1.5 rise
GRIPS	Onoff Beehive, 1lock-on, 135mm
SEATPOST	Onoff S3 0-R, diameter 31.6mm, length 400mm
SADDLE	MDK urban
FRONT BRAKE	Sram Level T, 2 piece caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pad
REAR BRAKE	Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
BRAKE LEVER	Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings
RIMS	MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes
SPOKES	CN round stainless steel
FRONT HUB	Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
REAR HUB	Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts, HG freehub

FRONT TIRE	Maxxis Gritter 29x2.5, single compound, 60TPI, wire bead
REAR TIRE	Maxxis Gritter 29x2.5, single compound, 60TPI, wire bead
CRANKSET	Race Face Aeffect-R ebike, 165mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
BOTTOM BRACKET	--
PEDALS	Urban pedal resin black
CHAIN	Sram SX Eagle, 12s, Powerlock
FRONT DERAILLEUR	--
REAR DERAILLEUR	Sram SX Eagle, 12s
SHIFT LEVERS	Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram PG-1210, 11-50T, 12s
MOTOR	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
BATTERY	Bosch Powertube 625Wh
DISPLAY	Bosch Intuvia 100 / Bosch Mini Remote / Bosch System Controller
DERAILLEUR HANGER	Sram UDH
OTHERS	Front light: 150LUX output DC 6-12V, waterproof Alloy cage. Rear Light: Fender Mount, w/ Reflective, e-bike version, 6-12V. Fenders: Alloy black MDK custom fenders. Rack: Alloy MDK rear Rack, Max loading 25kg. Kickstand: Massload KSA18-40
WEIGHT	--