

CHASER X

Crystal White / Black



FRAME STEALTH ALLOY • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT625Wh • **FORK** ROCKSHOX RECON SILVER SILVER, 150mm • **REAR SHOCK** ROCKSHOX DELUXE SELECT R • **BRAKES** SRAM DB8 • **WHEELS** MDK-HP1 • **REAR DERAILLEUR** SRAM SX EAGLE

CHASER X

Crystal White / Black

FRAME	Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 140mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard	REAR HUB	Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts, HG freehub
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm	FRONT TIRE	Maxxis Ikon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
REAR SHOCK	RockShox Deluxe Select R DebonAir, 205x60mm. Settings: Low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings	REAR TIRE	Maxxis Ikon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
SHOCK SETTINGS	DebonAir Progressive, Light compression, Linear rebound, 1 Token	CRANKSET	Race Face Aeffect-R ebike, 165mm
FORK	RockShox Recon Silver RL 29, 150mm, Solo Air, tapered steerer tube, Boost 15x110mm axle, 35mm steel stanchions, 44mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload	RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
FORK REMOTE	--	BOTTOM BRACKET	--
HEADSET	Onoff ZS44/ZS56, 1-1/8", 1.5" head tube, ACB sealed bearings, top 42x30x7x45°x45°, bottom 52x40x8x45°x45°	PEDALS	Urban pedal resin black
STEM	Onoff S3 30mm 0°, 6061 forged alloy, 31.8mm barbare	CHAIN	Sram SX Eagle, 12s, Powerlock
HANDLEBAR	Onoff S3 1.0 6061 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbare. L and XL size: 1.5 rise	FRONT DERAILLEUR	--
GRIPS	Onoff Beehive, 1lock-on, 135mm	REAR DERAILLEUR	Sram SX Eagle, 12s
SEATPOST	Onoff S3 0-R, diameter 31.6mm, length 400mm	SHIFT LEVERS	Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click
SADDLE	MDK urban	CASSETTE	Sram PG-1210, 11-50T, 12s
FRONT BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	MOTOR	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
REAR BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	BATTERY	Bosch Powertube 625Wh
BRAKE LEVER	Sram DB8, tool reach adjust, lever pivot bushings	DISPLAY	Bosch Intuvia 100 / Bosch Mini Remote / Bosch System Controller
RIMS	MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes	DERAILLEUR HANGER	Sram UDH
SPOKES	CN round stainless steel	OTHERS	Front light: 150LUX output DC 6-12V, waterproof Alloy cage. Rear Light: Fender Mount, w/ Reflective, e-bike version, 6-12V. Fenders: Alloy black MDK custom fenders. Rack: Alloy MDK rear Rack, Max loading 25kg. Kickstand: Massload KSA18-40
FRONT HUB	Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts	WEIGHT	--

CHASER X

Earth Red / Black / Flame Red



FRAME STEALTH ALLOY • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT625Wh • **FORK** ROCKSHOX RECON SILVER SILVER, 150mm • **REAR SHOCK** ROCKSHOX DELUXE SELECT R • **BRAKES** SRAM DB8 • **WHEELS** MDK-HP1 • **REAR DERAILLEUR** SRAM SX EAGLE

WX

Earth Red / Black / Flame Red

FRAME	Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 140mm travel, Forward Geometry, internal removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard	REAR HUB	Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts, HG freehub
SIZES	S: 380mm / M: 420mm / L: 450mm / XL: 490mm	FRONT TIRE	Maxxis Ikon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
REAR SHOCK	RockShox Deluxe Select R DebonAir, 205x60mm. Settings: Low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings	REAR TIRE	Maxxis Ikon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
SHOCK SETTINGS	DebonAir Progressive, Light compression, Linear rebound, 1 Token	CRANKSET	Race Face Aeffect-R ebike, 165mm
FORK	RockShox Recon Silver RL 29, 150mm, Solo Air, tapered steerer tube, Boost 15x110mm axle, 35mm steel stanchions, 44mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload	RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
FORK REMOTE	--	BOTTOM BRACKET	--
HEADSET	Onoff ZS44/ZS56, 1-1/8", 1.5" head tube, ACB sealed bearings, top 42x30x7x45°x45°, bottom 52x40x8x45°x45°	PEDALS	Urban pedal resin black
STEM	Onoff S3 30mm 0°, 6061 forged alloy, 31.8mm barbare	CHAIN	Sram SX Eagle, 12s, Powerlock
HANDLEBAR	Onoff S3 1.0 6061 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbare. L and XL size: 1.5 rise	FRONT DERAILLEUR	--
GRIPS	Onoff Beehive, 1lock-on, 135mm	REAR DERAILLEUR	Sram SX Eagle, 12s
SEATPOST	Onoff S3 0-R, diameter 31.6mm, length 400mm	SHIFT LEVERS	Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click
SADDLE	MDK urban	CASSETTE	Sram PG-1210, 11-50T, 12s
FRONT BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	MOTOR	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
REAR BRAKE	Sram DB8, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	BATTERY	Bosch Powertube 625Wh
BRAKE LEVER	Sram DB8, tool reach adjust, lever pivot bushings	DISPLAY	Bosch Intuvia 100 / Bosch Mini Remote / Bosch System Controller
RIMS	MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes	DERAILLEUR HANGER	Sram UDH
SPOKES	CN round stainless steel	OTHERS	Front light: 150LUX output DC 6-12V, waterproof Alloy cage. Rear Light: Fender Mount, w/ Reflective, e-bike version, 6-12V. Fenders: Alloy black MDK custom fenders. Rack: Alloy MDK rear Rack, Max loading 25kg. Kickstand: Massload KSA18-40
FRONT HUB	Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts	WEIGHT	--