

PRIME

Nimbus Grey / Obsidian Grey / Atomic Orange



FRAME STEALTH ALLOY • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT625Wh • **FORK** ROCKSHOX RECON SILVER RL, 120mm • **BRAKES** SRAM LEVEL T • **WHEELS** MAVIC E-CROSSRIDE • **REAR DERAILLEUR** SRAM SX EAGLE

PRIME

Nimbus Grey / Obsidian Grey / Atomic Orange

FRAME	Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, internal removable battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor
SIZES	XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm
REAR SHOCK	--
SHOCK SETTINGS	--
FORK	RockShox Recon Silver RL 29, 120mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 32mm steel stanchions, 42mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload
FORK REMOTE	--
HEADSET	Onoff ZS44/ZS56, 1-1/8", 1.5" head tube, ACB sealed bearings, top 42x30x7x45°x45°, bottom 52x40x8x45°x45°
STEM	Onoff S3 30mm 0°, 6061 forged alloy, 31.8mm barbore
HANDLEBAR	Onoff S3 1.0 6061 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbore. L and XL size: 1.5 rise
GRIPS	Onoff Beehive, 1lock-on, 135mm
SEATPOST	Onoff S3 0-R, diameter 31.6mm, length 400mm
SADDLE	MDK ebike black
FRONT BRAKE	Sram Level T, 2 piece caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pad
REAR BRAKE	Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
BRAKE LEVER	Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings
RIMS	Mavic E-CrossRide 29, 30mm internal width, welded, PFR, tubeless ready, 28 spokes
SPOKES	Mavic J-bend double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, HG freehub

FRONT TIRE	Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
REAR TIRE	Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
CRANKSET	Race Face Aeffect-R ebike, 160mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
BOTTOM BRACKET	--
PEDALS	--
CHAIN	Sram SX Eagle, 12s, Powerlock
FRONT DERAILLEUR	--
REAR DERAILLEUR	Sram SX Eagle, 12s
SHIFT LEVERS	Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram PG-1210, 11-50T, 12s
MOTOR	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
BATTERY	Bosch Powertube 625Wh
DISPLAY	Bosch Intuvia 100 / Bosch Mini Remote / Bosch System Controller
DERAILLEUR HANGER	Sram UDH
OTHERS	--
WEIGHT	--

PRIME

Crystal White / Midnight Blue / Flame Red



FRAME STEALTH ALLOY • **MOTOR** NEW BOSCH PERFORMANCE LINE CX (BDU384Y) SMART SYSTEM PT625Wh • **FORK** ROCKSHOX RECON SILVER RL, 120mm • **BRAKES** SRAM LEVEL T • **WHEELS** MAVIC E-CROSSRIDE • **REAR DERAILLEUR** SRAM SX EAGLE

PRIME

Nimbus Grey / Obsidian Grey / Atomic Orange

FRAME	Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, internal removable battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor
SIZES	XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm
REAR SHOCK	--
SHOCK SETTINGS	--
FORK	RockShox Recon Silver RL 29, 120mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 32mm steel stanchions, 42mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload
FORK REMOTE	--
HEADSET	Onoff ZS44/ZS56, 1-1/8", 1.5" head tube, ACB sealed bearings, top 42x30x7x45°x45°, bottom 52x40x8x45°x45°
STEM	Onoff S3 30mm 0°, 6061 forged alloy, 31.8mm barbore
HANDLEBAR	Onoff S3 1.0 6061 alloy, rise: 25mm, width: 800mm, 8° backsweep, 5° upsweep, 31.8mm barbore. L and XL size: 1.5 rise
GRIPS	Onoff Beehive, 1lock-on, 135mm
SEATPOST	Onoff S3 0-R, diameter 31.6mm, length 400mm
SADDLE	MDK ebike black
FRONT BRAKE	Sram Level T, 2 piece caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pad
REAR BRAKE	Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
BRAKE LEVER	Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings
RIMS	Mavic E-CrossRide 29, 30mm internal width, welded, PFR, tubeless ready, 28 spokes
SPOKES	Mavic J-bend double butted, contactless lacing
FRONT HUB	Mavic, Boost 15x110mm, IS 6 bolts
REAR HUB	Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts, HG freehub

FRONT TIRE	Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
REAR TIRE	Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
CRANKSET	Race Face Aeffect-R ebike, 160mm
RINGS	Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
BOTTOM BRACKET	--
PEDALS	--
CHAIN	Sram SX Eagle, 12s, Powerlock
FRONT DERAILLEUR	--
REAR DERAILLEUR	Sram SX Eagle, 12s
SHIFT LEVERS	Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click
CASSETTE	Sram PG-1210, 11-50T, 12s
MOTOR	New Bosch Performance Line CX Cruise (25Km/h) GEN4 SMART SYSTEM (BDU384Y)
BATTERY	Bosch Powertube 625Wh
DISPLAY	Bosch Intuvia 100 / Bosch Mini Remote / Bosch System Controller
DERAILLEUR HANGER	Sram UDH
OTHERS	--
WEIGHT	--